



Roller Shutter Door Kit 1460

high quality aluminium roll formed profiles,
extra strong,
for large roller shutter doors
and increased loads.

ferdinand brasellmann.aust
Diversity in profiles

Roller Shutter Door Kit 1460



The unique roll formed design of the 1460 roller door profile makes it the first choice for single wall roller shutter doors with increased loads, e.g. large door dimensions or high wind loads.

Also available in galvanized steel or stainless steel, material thickness 1.0 mm and 2.0 mm, anodized or powder colour coated on request.

• Technical Details

height: 97 mm (10.3 slats per metre)
thickness of slats: ~ 25 mm

• Maximum door width (wind class 3)

aluminium: up to 15500 mm
steel (option): up to 18500 mm
stainless steel (option): up to 18500 mm

• Applications

Large roller shutter doors
Strong wind load
Coastal environments

A door kit system that is easily tailor-made and even more simple to install. Each comprehensive kit provides an economical solution from a single source delivering a sophisticated solution.

All shipped systems comply with DIN EN 13241-1.

Scope of delivery:

- pre-assembled roller shutter with 1460 profiles
- completely finished springless drum
- 2 standard brackets
- 1 bearing
- galvanised guide rail with PVC wear strips
- springless direct drive system powered by GfA Elektromaten with digital limits and integrated frequency inverter (other drives on request)
- auto-up / hold-to-run close operation or impulse control with safety edge
- head seal (with double wall profile only)
- roller shutter assemblies on drum
- packaging
- optional: additional accessories available on request