



Roller Shutter Door Kit 1560

high quality aluminium roll formed profiles,
aesthetic appeal,
high visibility & ventilation capacity,
smooth & quiet operation.

ferdinand brasellmann.austri
Diversity in profiles

Roller Shutter Door Kit 1560



A strong and durable profile for single walled roller shutters providing 100 mm profile height. This unique profile offers smooth flat lines and fits in perfectly with architecturally designed facilities.

The option for large punched slots provides light permeability of up to 42%, features include open grid layout or polycarbonate window inserts.

Perfect for large shop front facades and commercial buildings.

Designed and manufactured in Germany, assembled in Australia.

• Technical Details

height: 100 mm (10 slats per metre)
Thickness of slats: ~ 19 mm

- **Maximum door width** (wind class 3)
aluminium: up to 8000 mm
steel (option): up to 9500 mm
stainless steel (option): up to 9500 mm

• Applications

Retail shop fronts
Commercial buildings
Coastal environments
Architecturally designed facilities

A door kit system that is easily tailor-made and even more simple to install. Each comprehensive kit provides an economical solution from a single source delivering a sophisticated solution.

All shipped systems comply with DIN EN 13241-1.

Scope of delivery:

- pre-assembled roller shutter with 1560 profiles
- completely finished springless drum
- 2 standard brackets
- 1 bearing
- galvanised guide rail with PVC wear strips
- springless direct drive system powered by GfA Elektromaten with digital limits and integrated frequency inverter (other drives on request)
- auto-up / hold-to-run close operation or impulse control with safety edge
- head seal (with double wall profile only)
- roller shutter assemblies on drum
- packaging
- optional: additional accessories available on request