



High Quality Aluminium Roll Formed
Roller Shutter Profile 1560

aesthetic appeal,
high visibility & ventilation capacity,
smooth & quiet operation.

ferdinand
brasellmann..au
Diversity in profiles

Roller Shutter Profile 1560



A profile for single walled roller shutters providing 100 mm profile height. This unique profile offers smooth flat lines and fits in perfectly with architecturally designed facilities.

The option for large punched slots provides light permeability of up to 42%, features include open grid layout or polycarbonate window inserts.

Perfect for large shop front facades and commercial buildings.

Designed and manufactured in Germany, assembled in Australia.

• material thickness [mm]

	1.00*	1.25	1.50
aluminium, bright	•	• ^p	•
aluminium, powder colour coated*	•	• ^p	•
aluminium, plastic colour coated*	•	•	
aluminium, anodized 3μ*	•	•	•
aluminium, anodized 20μ*	•	•	•
steel, galvanized*	•	• ^p	•
steel, powder colour coated*	•	• ^p	•
stainless steel*	•	•	

* on request

^p = perforated plate available

• technical details

height: 100 mm (10 slats per metre)
thickness of slats: ~ 19 mm

• weight (at 1.00 mm)

aluminium: ~ 0.47 kg/m (4.7 kg/m²)
steel*, stainless steel*: ~ 1.37 kg/m (13.7 kg/m²)

• maximum door width (wind class 2, without storm hooks)

	1.00*	1.25	1.5
aluminium	5200	5600	6100
steel, * stainless steel*	7000	7600	8200

• calculated bale diameter [mm]

opening height	tube diameter [mm]						
	159	169	194	219	267	324	368
3 m	330	330	340	360	400	440	470
3.50 m	360	360	360	390	420	460	470
4 m	360	360	380	400	420	460	470
4.50 m	380	380	390	420	430	480	510
5 m	380	400	400	420	450	500	510
6 m	420	440	430	460	490	520	530
7 m	460	460	470	570	510	540	550
8 m	460	480	510	500	520	540	570