



## Roller Shutter Door Kit 95R Standard

for light and  
heat-insulating roller shutters.

ferdinand  
brasellmann.a.u  
Diversity in profiles

# Roller Shutter Door Kit 95 R

## Standard



95 R is an insulated roller shutter profile with the outstanding feature of reduced weight. The standard lath in 0.38 mm galvanized steel with transparent coating is comparable in weight to a 1.100 D aluminium lath.

Thanks to the slightly curved form, this profile moves very quietly.

The recommended choice for roller shutter doors especially when low self-weight and small bale diameter are required.

Available in steel, with coloured coating in all RAL-colours or coil coating in colours like RAL 3000, 5010, 6009, 7005, 7016, 7044, 8014, 9002, 9006, 9007 and 9016 on request.

Designed and manufactured in Germany, assembled in Australia.

### • Technical Details

insulated PU-filled profile

material: 0.38 mm galvanized steel  
0.47 mm aluminium (on request)

slats on 1 m height: 10.1

thickness of slats: ca. 23 mm

### • Maximum door width (wind class 3)

steel: W 6500 mm x H 5500 mm

aluminium (on request): W 5000 mm x H 3500 mm /  
W 4000 mm x H 5250 mm

Fast, uncomplicated construction of roller door systems can be made easier by tailor-made, complete construction sets for roller shutter doors in which supply of all needed parts from a single source enables economical solutions as part of a sophisticated system.

All shipped systems comply with DIN EN 13241-1.

### Scope of delivery:

- pre-assembled roller shutter with profiles type 95 R
- completely finished tube
- 2 standard brackets
- 1 bearing
- galvanised guide rail with PVC strips
- springless direct drive system powered by GfA Elektromaten with digital top switch and integrated frequency converter (other drives on request)
- dead man's control or impulse control with connection cable and CEE plug
- head seal (with double walled profiles only)
- roller shutter wound on tube
- wrapping (board)
- optional: extensive additional accessories